

## **ELECTRIC VEHICLE**

applications are wide and varied with many durability & power demands placed firmly on the batteries shoulders.

HAZE ELECTRIC
VEHICLE AGM always
delivers when you need it,
whatever your DC
requirement in general EV
applications.




Tough ABS case with INSERT TERMINALS as standard, smaller sizes with FASTON.

Special Active Material
Formulation & AGM Technology
delivers cranking amps, general
power and long/deep
discharges.

GOOD CYCLE LIFE and resistance to mechanical stress and the elements all in one battery.

	Dimensions mm - kg						Dimensions Inches - lbs							Cold Cranking Amps		
			Height	Height	Height				Height	Height	Height		20°C	0°C	-18°C	
	Length	Width	Auto	Insert	Battery	Weight	Length	Width	Auto	Insert	Battery	Weight	(68°F)	(32°F)	(0°F)	
HZB-EV12-100	306	168	229	212	211	30.4	12.03	6.61	9.02	8.35	8.31	67.03	861	751	546	

			Reserve Capacity - Mins						Capacity - Ampere Hour*							
	Volts	Thread size mm	75 Amps	25 Amps	20 Amps	15 Amps	8 Amps	100 Hr	48 Hr	20 Hr	10 Hr	5 Hr	3 Hr	1 Hr		
HZB-EV12-100	12	8	46	178	236	332	689	124	116	107.8	94.9	83.9	75.6	61.3		



EV Charging - To obtain maximum cycle life from your EV battery it is important that a suitable charging profile is used. For information about the Haze range of chargers and the Haze recommended charging profile contact your local Haze distributor.

**NOTE**: All Haze AGM batteries are true cycling batteries, plate chemistry is specifically for cyclic applications.

HAZE ELECTRIC VEHICLE AGM delivers maximum capacity within five cycles and keeps delivering long after the others are on the scrap heap. HAZE R&D has resulted in SPECIAL CHEMICAL and PROCESS technology to ensure consistency and performance.